



REV	DESCRIPTION
1	INITIAL DESIGN
2	REVISED AND REDRAWN
3	CHANGED TO 4 PIN TO 1.5K. SW
4	
5	
6	
7	
8	
9	
10	
11	
12	
13	
14	
15	
16	
17	
18	
19	
20	
21	
22	
23	
24	
25	
26	
27	
28	
29	
30	
31	
32	
33	
34	
35	
36	
37	
38	
39	
40	
41	
42	
43	
44	
45	
46	
47	
48	
49	
50	
51	
52	
53	
54	
55	
56	
57	
58	
59	
60	
61	
62	
63	
64	
65	
66	
67	
68	
69	
70	
71	
72	
73	
74	
75	
76	
77	
78	
79	
80	
81	
82	
83	
84	
85	
86	
87	
88	
89	
90	
91	
92	
93	
94	
95	
96	
97	
98	
99	
100	

- NOTES:
- Q102 AND Q302 ARE HEATSINK TOGETHER WITH A DUAL TUBE COOLER.
  - Q111 AND Q112 ARE HEATSINK TO THE BOARD MOUNTING BRACKET.
  - THIS SCHEMATIC APPLIES TO UNITS WITH SERIAL NUMBERS 99423 AND FOLLOWING.
  - ALL RESISTORS ARE .25W EX WITH VALUES IN OHMS UNLESS OTHERWISE SPECIFIED.
  - ALL CAPACITOR VALUES IN MICROFARADS UNLESS OTHERWISE SPECIFIED.
  - CHANNEL 1 MAIN BOARD COMPONENTS NUMBERED 100-199.
  - CHANNEL 2 MAIN BOARD COMPONENTS NUMBERED 200-299.
  - CHANNEL 1 OFF BOARD COMPONENTS NUMBERED 300-399.
  - CHANNEL 2 OFF BOARD COMPONENTS NUMBERED 400-499.
  - COMMON MAIN BOARD COMPONENTS NUMBERED 1-99.
  - COMMON OFF BOARD COMPONENTS NUMBERED 500-599.
  - DC VOLTAGES SHOWN APPLY TO NORMAL QUIESCENT OPERATING CONDITIONS.
  - MAJOR FEEDBACK PATH DEPICTED BY A HEAVY LINE.

**INACTIVE**  
For Reference Use Only

<b>CROWN</b>		1718 M. MISHANAKA RD.	PHONE
SC, D150A2		ELKHART, INDIANA 46514	(819) 294-8000
DRAWN	JH	3-9-80	SCALE NONE
CHECKED	JF	3-24-80	PROJ E11
APPROVED	CG	3-22-80	SUPERSEDES
NEXT ASSEMBLY			C.P.N.
			J0123-0

REV	DESCRIPTION	DATE	BY	APP
(A)	REVISED AND REDRAWN	2/18/80	LEB	JG
(B)	REVISION FOR CH. 100	4/18/80	CHB	JG
(C)	CHANGED TO 4 PIN TO 1.5K. SW	3-9-80	JH	JG
(D)				
(E)				
(F)				